MHC Intelligent Multi-layer Cutting Machine

TECHNICAL PARAMETERS

. 1

Model.NO	MHC-2025	MHC-2325
Cutting Area (w*I)	1950*2300mm	2230*2300mm
Machine Dimensions	5900*3250*2150mm	5900*3550*2150mm
Weight	4.5T	4.8T
Max Cutting Speed	70m/min	
Cutting Thickness	7/11cm	
Cutting Accuracy	≤±1mm	
Power	16-25kw	

Concerned in

Software **Control System Cooling System** Sharpen Way Max Speed Motor & Driver Machine Power Air Pressure Supply

Cutting Style

RLK 润金

Straight Knife Cutting

YINENG Cutting program

YINENG CUT V4.0

Auto Air Cooling System

Sharpening stone System

4500rpm/min

Panasonic Servo Motors & Drivers

AC380V/50Hz


0.55MPa 160L/min

Five Systems of Excellence



Electrical System

The electrical system of the whole machine adopts an automatic control system, which effectively protects the stable operation of the equipment through a large number of imported components, and ensures the cutting accuracy with highprecision and highspeed servo drive system.




Transmission System

The transmission mode adopts high-precision rack and gear transmission system, which has high transmission accuracy, stable start and stop, and long service life.



Cutting head

The cutting head is derived from the Japanese principle. The core components of the machine head have high hardness, light weight, long service life, high stability, and effectively guarantee the cutting effect during high-speed operation.



APPLICATION INDUSTRIES

Clothing, home textiles, medical, inflatables, sofas, shoes and hats, luggage, plush toys, car interiors and other applications.


















Machine

One-piece machine body, annealing and stressrelieving treatment can ensure the body will not deform, with stronger wear resistance and higher precision.

Controll System

Cutting control system CutV4.0 independ-ently developed,Automatically identify symmetrical graphics, increase the cutting process of symmetrical graphics, identify symmetrical graphics in batches according to the symmetrical template, support the mutual conversion of I notch and V notch, and the size setting of I notch and V notch.



